

# Bluelab Product Information Sheet

for Distributors of Bluelab Nutrient Solution Testers and Accessories

<b>Product Name:</b>	<b>Bluelab Combo Meter</b>
<b>Product Code:</b>	<b>METCOM</b>
<b>UPC Code:</b>	9421024920036
<b>Country of Origin:</b>	New Zealand
<b>Tariff Code:</b>	9027.80
<b>Shipping Quantity:</b>	10 kg = 21 units / 25 kg = 50 units
<b>Packaging Information:</b>	
<b>Packaged Weight:</b>	0.48 kg / 1.06 lb
<b>Packaged Length:</b>	180 mm / 7.086 in
<b>Packaged Width:</b>	110 mm / 4.33 in
<b>Packaged Height:</b>	83 mm / 3.267 in



**Product images available for Screen or Web use:**

- Bluelab-ComboMeter-MR-flat-RGB.jpg
- Bluelab-ComboMeter-WEB.jpg
- Bluelab-ComboMeter-Web-sml.jpg

**Product images available for PRINT:**  
*Note: these images are high resolution in CMYK.*

- Bluelab-ComboMeter-MR-flat-CMYK.tif

**Sales Description:**  
*NOTE: this copy can be used in brochures, catalogues or online*

**It's all you need for simple and reliable crop management and it's all within arm's reach!**

The Bluelab Combo Meter is a conductivity, pH and temperature meter all in one.

The Bluelab pH Probe and the Bluelab Conductivity/Temperature Probe are simply placed into the solution and the selected reading is displayed on screen.

As the Bluelab Combo Meter is portable and does not require a power supply to operate, it can be used anytime and anywhere to help you manage your crops daily nutrient requirements.

Calibration of the pH is simple with the push buttons on the meter and fresh calibration solutions. Conductivity and temperature do not need to be calibrated as this is locked in during manufacture.


Display options available in °C, °F, EC, CF, ppm 500 and ppm 700.

**Features:**

- Lightweight and portable
- Large easy to read display
- No calibration required for conductivity and temperature
- Successful pH calibration indicator
- Replaceable double junction pH probe
- Low battery indicator
- Simple push button pH calibration
- Battery operated
- Auto off function

**Technical Specifications:**

<b>Measurement Range:</b>	0.0 – 14.0 pH, 0.0 – 9.9 EC, 99 CF 0 – 4950 ppm (500 ppm / TDS) 0 – 6930 ppm (700 ppm) 0 – 50°C / 32 – 122°F
<b>Resolution:</b>	0.1 pH, 0.1 EC, 1 CF 10 ppm (500 ppm) 10 ppm (700 ppm) 1°C / 1°F
<b>Accuracy at 2.77 EC and 25°C / 77°F:</b>	± 0.1 pH, ± 1 EC, ± 1 CF, ± 50 ppm (500 ppm) ± 70 ppm (700 ppm) ± 1°C / ± 2°F
<b>Automatic Temperature Compensation:</b>	Yes
<b>Operating Environment:</b>	0 – 50°C / 32 – 122°F
<b>Calibration:</b>	Not required for conductivity. pH requires two point, pH 7.0 & pH 4.0 or pH 10.0 calibration
<b>Power Source:</b>	2 x AAA alkaline batteries
<b>User Manual Languages Available:</b>	English; Español; Français; Nederlands; Deutsch
<b>Certifications:</b>	CE and FCC

<b>Product Guarantee:</b>	
Five year free repair or replacement guarantee. * Six months for pH Probe.	

{This Product Information Sheet is NOT intended for distribution to end users.}